

850VA UPS mit AVR, Zukunftsweisend!

EG-UPS-B850

ULTIMATE DEFENCE

- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use



Eigenschaften

- Automatische Ausgangsspannungsregulierung (AVR)
- LED-Statusanzeige
- Kurzschlussicherung
- Überspannungs- und Spannungsspitzenabsicherung sowie Blitzschutz
- Hörbare und sichtbare Alarmer
- Absicherung vor Überladung und Tiefentladung

Verpackungsdetails

Stückzahl pro Karton	4
Karton Volumen, m ³	0.045356
Kartongewicht, kg	21.4
Abmessungen Verpackung (LxBxH):	338x147x210 mm
Abmessungen Umkarton (LxBxH):	580x340x230 mm
Ursprungsland	CN
EAN Code	8716309087070
Zolltarif-Nr.:	8504408590

Lieferumfang

UPS
User manual

CE-Erklärung



Spezifikationen

UPS type: line interactive
Input: AC 220V±25%, 50Hz/60Hz ±10%
Output: AC 220V±10%, 50Hz/60Hz ±0.5% (on battery)
Switching time: 4-8ms
Backup time: up to 20 mins (depends on the load)
Battery: 151 x 65 x 95 mm, sealed lead-acid 12V/8Ah x 1 pc

Charge time: up to 12 hours
Sockets: 2 x Schuko output (CEE 7/4)
Operating conditions: 0°C~40°C, at humidity 10~90%RH non condensing

Power: 850 VA (510 W)
Dimensions: 280 x 140 x 100 mm
Product weight: 5.5 kg
"Cold-start" function

Systemvoraussetzungen

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.