

650 VA "Basic 650" UPS, Shuko output sockets, black

EG-UPS-B650

ULTIMATE DEFENCE

- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use



Īpašības

- Uninterruptable 650 VA power supply for PC's
- Automatic output voltage regulation (AVR)
- LED status indication
- Short circuit protection
- Overload, surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection

Packaging

Skaitis iepakojumā, gab.
Iepakojuma izmērs, kub.m
Iepakojuma svars, kg
Individual package size LxWxH:
Carton size LxWxH:
Izcelsmes valsts
Svītrkods
Customs code

4
0.043792
19.2
338x147x210 mm
560x340x230 mm
CN
8716309087087
8504408590

Iepakojuma saturs

UPS
User manual

Sertifikāti



Specifikācija

UPS type: line interactive
Input: AC 220V±28%, 50Hz/60Hz ±10%
Output: AC 220V±10%, 50Hz/60Hz ±0.5% (on battery)
Switching time: no more than 10 ms
Backup time: up to 20 mins (depends on the load)
Battery: 151 x 65 x 95 mm, sealed lead-acid 12V/7Ah x 1 pc

Charge time: up to 12 hours
Sockets: 2 x Schuko output (CEE 7/4)
Operating conditions: 0°C~40°C, at humidity 10~90%RH non condensing

Power: 650 VA (390 W)
Dimensions: 100 x 280 x 140 mm
Product weight: 4.3 kg
"Cold-start" function

Sistēmas prasības

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.