

UPS avansat cu AVR, 650 VA

EG-UPS-B650

ULTIMATE DEFENCE

- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use



Features

- Sursa de alimentare neinteruptibila de 650 VA pentru computere
- Reglare automata a tensiunii de iesire (AVR)
- Indicator LED de stare
- Protectie pentru scurt circuite
- Protectie de supratensiune, spike si fulgere
- Alarmer vizuale si audio
- Protectie pentru supraincarcare si supradescarcare

Packaging

Q'ty in crtn, pcs	4
Crtn volume, CUM	0.043792
Crtn weight, kgs	19.2
Individual package size LxWxH:	338x147x210 mm
Carton size LxWxH:	560x340x230 mm
Country of origin	CN
Barcode	8716309087087
Customs code	8504408590

Package contents

UPS
User manual

Certificates



Specifications

UPS type: line interactive
Input: AC 220V±28%, 50Hz/60Hz ±10%
Output: AC 220V±10%, 50Hz/60Hz ±0.5% (on battery)
Switching time: no more than 10 ms
Backup time: up to 20 mins (depends on the load)
Battery: 151 x 65 x 95 mm, sealed lead-acid 12V/7Ah x 1 pc

Charge time: up to 12 hours
Sockets: 2 x Schuko output (CEE 7/4)
Operating conditions: 0°C~40°C, at humidity 10~90%RH non condensing

Power: 650 VA (390 W)
Dimensions: 100 x 280 x 140 mm
Product weight: 4.3 kg
"Cold-start" function

System requirements

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.