

UPS avansat cu AVR, 800 VA

EG-HI-PS800-01

- Easily combine with any 12V battery for 24/7 Active backup power
- Protects your sensitive and valuable equipment
- Pure sine wave output Perfect for solar panel installations and other sensitive equipment
- Compact and reliable ideal for home and small office use



Features

- Sursa de alimentare neintreruptibila de 800 VA pentru computere
- Reglare automata a tensiunii de iesire (AVR)
- Indicator LED de stare
- Protectie pentru scurt circuite
- Protectie de supratensiune, spike si fulgere
- Alarmer vizuale si audio
- Protectie pentru supraincarcare si supradescarcare

Packaging

Q'ty in crtn, pcs	2
Crtn volume, CUM	0.04907375
Crtn weight, kgs	17.4
Individual package size LxWxH:	415x198x250 mm
Carton size LxWxH:	430x415x275 mm
Country of origin	CN
Barcode	8716309087254
Customs code	8504408590

Package contents

Home Inverter
User manual

Certificates



Specifications

UPS type: line interactive, pure sinewave
Input: AC 140 275V, 50Hz/60Hz $\pm 10\%$
Output: AC 220 V $\pm 10\%$, 50Hz/60Hz $\pm 5\%$ (on battery)
Switching time: less than 4 ms
Battery: external, sealed lead-acid 12 VDC, up to 300 Ah (not included)

Charge time: up to 12 hours
Sockets: 2 x Schuko output (CEE 7/4)
Operating conditions: 0°C~40°C, at humidity 10~90%RH non condensing

Power: 800 VA (480 W)
Dimensions: 390 x 160 x 240 mm
Net weight: 8.0 kg

System requirements

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.