

Home pure sine inverter with AVR and battery management function, 800VA



- Protects your sensitive and valuable equipment
- Pure sine wave output Perfect for solar panel installations and other sensitive equipment
- Compact and reliable ideal for home and small office use



Specifikacije

UPS type: line interactive, pure sinewave Input: AC 140 275V, 50Hz/60Hz $\pm 10\%$ Output: AC 220 V \pm 10 %, 50Hz/60Hz $\pm 5\%$ (on battery)

Switching time: less than 4 ms

Battery: external, sealed lead-acid 12 VDC, up to 300 Ah (not included)

Charge time: up to 12 hours

Sockets: $2 \times Schuko output (CEE 7/4)$

Operating conditions: 0°C~40°C, at humidity 10~90%RH non condensing

Power: 800 VA (480 W)

Dimensions: 390 x 160 x 240 mm

Net weight: 8.0 kg

Karakteristike

- 800 VA Pure sinewave Home Inverter with AVR and battery management function
- Can be used as UPS when external 12V battery is connected
- High charging current (up to 15 A), recharges the large capacity batteries quickly
- "Smart charging technology" Intelligent charger for batteries with the "training" mode
- Protection against short circuit, overload, overvoltage or undervoltage
- Modular CPU controlled circuit with self-diagnostics cycle at every start-up

Pakovanje i slike

Q'ty in crtn, pcs Crtn volume, CUM Crtn weight, kgs Individual package size LxWxH: Carton size LxWxH: Country of origin Barcode Customs code 2 0.04907375 17.4 415x198x250 mm 430x415x275 mm CN 8716309087254 8504408590

Package contents

Home Inverter User manual

Sertifikati











Sistemski zahtevi

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.