Onduleur intelligent, 800 VA

EG-HI-PS800-01

- Onduleur externe
- Protège vos équipements sensibles
- Protection primaire ou redondante 24H/24
- Compacte et fiable



Spécificités

UPS type: line interactive, pure sinewave
Input: AC 140 275V, 50Hz/60Hz ±10%
Output: AC 220 V ± 10 %, 50Hz/60Hz ±5 % (on battery)
Switching time: less than 4 ms
Battery: external, sealed lead-acid 12 VDC, up to 300 Ah (not included)

Charge time: up to 12 hours
Sockets: 2 x Schuko output (CEE 7/4)
Operating conditions: 0°C~40°C, at humidity 10~90%RH non condensing

Power: 800 VA (480 W)
Dimensions: 390 x 160 x 240 mm
Net weight: 8.0 kg

Propriétés

- 800 VA UPS with pure sinewave output
- Modular CPU controlled circuit
- High charging current (max. 15 A), recharges the large capacity batteries quickly
- Technologie "Smart Charge" ultra rapide
- Multi-protection
- Auto Diag
- Affichage LCD
- Solution de protection pour tous.

Packaging

Q'ty in crtn, pcs	2
Crtn volume, CUM	0.04907375
Crtn weight, kgs	17.4
Individual package size LxWxH:	415x198x250 mm
Carton size LxWxH:	430x415x275 mm
Country of origin	CN
Barcode	8716309087254
Customs code	8504408590

Contenu du colis

Home Inverter
User manual

Certificats

Configuration requise

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.

Copyright © 2009–2024, Gembird Software Ltd.

Wittevrouwen 56 | 1358CD Almere | The Netherlands | Phone: +31-36-5211588
www.energenie.com | postmaster@energenie.com