

2000VA pure sine wave UPS, LCD display, USB, black

EG-UPS-PS2000-01

ULTIMATE DEFENCE

- Pure sine wave output
- Provide backup power Prevents data loss
- Protects your sensitive and valuable equipment
- Perfect support for solar panel installations and other sensitive equipment that requires pure sinewave input
- Compact and reliable ideal for home and small office use



Features

- Uninterruptable power supply with pure sine wave output
- USB interface
- Automatic AC voltage regulation (AVR)
- Intelligent overload and short-circuit protection
- Audible and visual alarms
- LCD display and LED status indication
- Internal battery with overcharge and over-discharge protection

Packaging

| | |
|--------------------------------|----------------|
| Q'ty in crtn, pcs | 1 |
| Crtn volume, CUM | 0,04125 |
| Crtn weight, kgs | 20 |
| Individual package size LxWxH: | 492x316x236 mm |
| Carton size LxWxH: | 500x250x330 mm |
| Country of origin | CN |
| Barcode | 8716309087353 |
| Customs code | 8504408490 |

Package contents

UPS
Power cord
Spare fuse

Specifications

Type: line interactive
Waveform: sine, 5% distortion at linear load, PF > 0.8 (on battery)

Input: AC 220V±25%, 50Hz/60Hz ±10%
Output: AC 220V±12%, 50Hz/60Hz ±1% (AC 220V±5% at inverter mode)
Switching time: μ to 10 ms
Backup time: 10...30 mins (depends on the load)
Battery: 151 x 65 x 94 mm, sealed lead-acid 12V/9Ah, F2 terminals x 3 pcs
Charge time: up to 12 hours
Sockets: C14 input, 4 outputs x C13; USB-BF connector

System requirements

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.

Certificates

