2000VA pure sine wave UPS, LCD display, USB, black

EG-UPS-PS2000-01

ULTIMATE DEFENCE

- Pure sine wave output
- Provide backup power Prevents data loss
- Protects your sensitive and valuable equipment
- Perfect support for solar panel installations and other sensitive equipment that requires pure sinewave input
- Compact and reliable ideal for home and small office use



Jellemzők

- Uninterruptable power supply with pure sine wave output
- USB interface
- Automatic AC voltage regulation (AVR)
- Intelligent overloadand short-circuit protection
- Audible and visual alarms
- LCD display and LED status indication
- Internal battery with overcharge and over-discharge protection

Részletes leírás

Type: line interactive
Waveform: sine, 5% distortion at linear load, PF > 0.8 (on battery)

Input: AC 220V±25%, 50Hz/60Hz ±10%
Output: AC 220V±12%, 50Hz/60Hz ±1% (AC 220V±5% at inverter mode)

Switching time: u to 10 ms
Backup time: 10...30 mins (depends on the load)
Battery: 151 x 65 x 94 mm, sealed lead-acid 12V/9Ah, F2 terminals x 3 pcs

Charge time: up to 12 hours
Sockets: C14 input, 4 outputs x C13; USB-BF connector
Operating conditions: 0°C~40°C, at humidity 10~90%RH non condensing

Power: 2000VA (1600 W)
Charging current: up to 1.2 A
Noise: < 50 dB at 1 m distance
Dimensions: 412 x 215 x 144 mm
Product weight: 18.5 kg
"Cold-start" function

Packaging

Darab / karton	1
Csomag térfogata, m3	0.04125
Karton súlya, kg	21
Individual package size LxWxH:	492x316x236 mm
Carton size LxWxH:	500x250x330 mm
Származási hely	CN
Vonalkód	8716309087353
Customs code	8504408590

Csomag tartalom

UPS
Power cord
Spare fuse

Tanúsítványok

Rendszerkövetelmények

In order to work correclty, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.

Copyright © 2009–2024, Gembird Software Ltd.

Wittevrouwen 56 | 1358CD Almere | The Netherlands | Phone: +31-36-5211588
www.energenie.com | postmaster@energenie.com