UPS cu unda sinusoidala pura, 3000VA, USB

EG-UPS-PS3000-01



ULTIMATE DEFENCE

- Pure sine wave output
- Provide backup power Prevents data loss
- Protects your sensitive and valuable equipment
- Perfect support for solar panel installations and other sensitive equipment that requires pure sinewave input
- Compact and reliable ideal for home and small office use

Specifications

Type: line interactive
Waveform: sine, 5% distortion at linear load, PF > 0.8
Input: AC 220V±25%, 50Hz/60Hz ±10%
Output: AC 220V±12%, 50Hz/60Hz ±1% (AC 220V±5% at inverter mode)

Switching time: up to 10 ms typically
Backup time: 10...30 mins (depends on the load)
Battery: 151 x 65 x 94 mm, sealed lead-acid 12V/9Ah, F2 terminals x 4 pcs

Charge time: up to 12 hours
Sockets: C14 input, 4 outputs x C13; USB-BF connector
Operating conditions: 0°C~40°C, at humidity 10~90%RH non condensing

Power: 3000VA (2400 W)
Charging current: up to 1.7 A
Noise: < 50 dB at 1 m distance
Dimensions: 467 x 336 x 190 mm
Product weight: 28.1 kg
Fuse: 15A
"Cold-start" function

Features

- Sursa de alimentare neintreruptibila cu conector de iesire unda sinusoidala pura
- Interfata USB
- Reglare automata a tensiunii AC (AVR)
- Protectie inteligenta pentru supraincarcare si scurt circuite

- Alarme vizuale si audio
- Indicator LED pentru stare si display LCD
- Baterie interna cu protectie pentru supraincarcare si supra-descarcare.

Packaging

Q'ty in crtn, pcs	1
Crtn volume, CUM	0.09792
Crtn weight, kgs	32.15
Individual package size LxWxH:	592x462x320 mm
Carton size LxWxH:	600x340x480 mm
Country of origin	CN
Barcode	8716309087377
Customs code	8504408590

Package contents

UPS
Power input cord
Power IEC output cord x 2 pcs

Certificates

System requirements

In order to work correclty, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.

Copyright © 2009–2024, Gembird Software Ltd.

Wittevrouwen 56 | 1358CD Almere | The Netherlands | Phone: +31-36-5211588
www.energenie.com | postmaster@energenie.com