

## 3000VA Sinus Signalform UPS, USB

EG-UPS-PS3000-01

### ULTIMATE DEFENCE

- Pure sine wave output
- Provide backup power Prevents data loss
- Protects your sensitive and valuable equipment
- Perfect support for solar panel installations and other sensitive equipment that requires pure sinewave input
- Compact and reliable ideal for home and small office use



### Eigenschaften

- Automatische Ausgangsspannungsregulierung (AVR)
- Reiner Sinus Signalform
- LED-Statusanzeige
- Kurzschlussicherung
- Überspannungs-und Spannungsspitzenabsicherung sowie Blitzschutz
- Hörbare und sichtbare Alarmer
- Absicherung vor Überladung und Tiefentladung

### Verpackungsdetails

|                                 |                |
|---------------------------------|----------------|
| Stückzahl pro Karton            | 1              |
| Karton Volumen, m <sup>3</sup>  | 0.09792        |
| Kartongewicht, kg               | 32.15          |
| Abmessungen Verpackung (LxBxH): | 592x462x320 mm |
| Abmessungen Umkarton (LxBxH):   | 600x340x480 mm |
| Ursprungsland                   | CN             |
| EAN Code                        | 8716309087377  |
| Zolltarif-Nr.:                  | 8504408590     |

### Lieferumfang

UPS  
Power input cord  
Power IEC output cord x 2 pcs

### CE-Erklärung



### Spezifikationen

Type: line interactive  
Waveform: sine, 5% distortion at linear load, PF > 0.8  
Input: AC 220V±25%, 50Hz/60Hz ±10%  
Output: AC 220V±12%, 50Hz/60Hz ±1% (AC 220V±5% at inverter mode)

Switching time: up to 10 ms typically  
Backup time: 10...30 mins (depends on the load)  
Battery: 151 x 65 x 94 mm, sealed lead-acid 12V/9Ah, F2 terminals x 4 pcs

Charge time: up to 12 hours  
Sockets: C14 input, 4 outputs x C13; USB-BF connector  
Operating conditions: 0°C~40°C, at humidity 10~90%RH non condensing

Power: 3000VA (2400 W)  
Charging current: up to 1.7 A  
Noise: < 50 dB at 1 m distance  
Dimensions: 467 x 336 x 190 mm  
Product weight: 28.1 kg  
Fuse: 15A  
"Cold-start" function

### Systemvoraussetzungen

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.