

Rack UPS, 2000 VA, black

EG-UPSRACK-12

ULTIMATE DEFENCE

- Protects important data from power cuts
- Protects valuable equipment
- Protects users



Características

- Automatic output voltage regulation (AVR)
- Rack 3.4U metal case
- USB control interface
- LCD display
- Short circuit protection
- Compatible with power generators of any brand
- Overload, surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection

Embalaje

Cantidad por caja, pcs	1
Volumen caja, M3	0.076632
Peso caja, kgs	25.06
Medidas cajas individuales LxWxH:	525x400x225 mm
Medidas caja LxWxH	620x515x240 mm
País de origen	CN
Código de barras	8716309087735
codigo de aduanas	8504408590

Contenido de la caja

UPS
Power cord
USB cable
Software CD
Spare fuse

Certificados



Especificaciones

UPS type: line interactive, pure sine wave
 Input: 220V AC $\pm$ 25%, 50Hz / 60Hz $\pm$ 10%
 Output: 220V AC $\pm$ 10%, 50Hz / 60Hz $\pm$ 0.5% (on battery)
 Output power factor: 0.8
 Inverter output efficiency (resistive load): 85%, any load type is allowed

Switching time: no more than 10 ms (typically 6 ms)
 Backup time: 8...20 mins (depends on the load)
 Battery: 151 x 65 x 95 mm, sealed lead-acid 12 V / 9 Ah / 2.3 kg x 3 pcs

Charge time: up to 12 hours
 Sockets: input IEC C14, outputs: Schuko EU type x 1 pc, IEC C13 x 6 pcs

Operating conditions: 0°C~40°C, at humidity 10~90%RH non condensing

Noise: < 45 dB (at 1 meter distance)
 Power: 2000 VA (1600 W)
 Dimensions: 440 x 410 x 132 mm
 Product weight: 19.8 kg
 "Cold-start" function

Requisitos del sistema

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.