Rack UPS, 2000 VA, black

EG-UPSRACK-12



ULTIMATE DEFENCE

- Protects important data from power cuts
- Protects valuable equipment
- Protects users

Techniniai duomenys

UPS type: line interactive, pure sine wave
Input: 220V AC ± 25%, 50Hz / 60Hz ± 10%
Output: 220V AC ± 10%, 50Hz / 60Hz ± 0.5% (on battery)
Output power factor: 0.8
Inverter output efficiency (resistive load): 85%, any load type is allowed

Switching time: no more than 10 ms (typically 6 ms)
Backup time: 8...20 mins (depends on the load)
Battery: 151 x 65 x 95 mm, sealed lead-acid 12 V / 9 Ah / 2.3 kg x 3 pcs

Charge time: up to 12 hours
Sockets: input IEC C14, outputs: Schuko EU type x 1 pc, IEC C13 x 6 pcs

Operating conditions: 0°C~40°C, at humidity 10~90%RH non condensing

Noise: < 45 dB (at 1 meter distance)
Power: 2000 VA (1600 W)
Dimensions: 440 x 410 x 132 mm
Product weight: 19.8 kg
"Cold-start" function

Funkcijos

- Automatic output voltage regulation (AVR)
- Rack 3.4U metal case
- USB control interface
- LCD display
- Short circuit protection
- Compatible with power generators of any brand
- Overload, surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection

Packaging

Dėžių kiekis, vnt	1
Dėžių dydis, CUM	0.076632
Dėžių svoris, kg	25.06
Individual package size LxWxH:	525x400x225 mm
Kilmės šalis	620x515x240 mm
Kilmės šalis	CN
Brūkšninis kodas	8716309087735
Customs code	8504408590

Pakuotės turinys

UPS
Power cord
USB cable
Software CD
Spare fuse

Sertifikatai

Sistemos reikalavimai

In order to work correclty, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.

Copyright © 2009–2024, Gembird Software Ltd.

Wittevrouwen 56 | 1358CD Almere | The Netherlands | Phone: +31-36-5211588
www.energenie.com | postmaster@energenie.com