

Rack 2000VA UPS

EG-UPSRACK-12

ULTIMATE DEFENCE

- Protects important data from power cuts
- Protects valuable equipment
- Protects users



Eigenschaften

- Automatische Ausgangsspannungsregulierung (AVR)
- Rack 3.4U Metallgehäuse
- USB-Schnittstelle
- LCD-Statusanzeige
- Kurzschlussicherung
- Kompatibel mit allen Stromgeneratoren aller Marken
- Überspannungs- und Spannungsspitzenabsicherung sowie Blitzschutz
- Hörbare und sichtbare Alarme
- Absicherung vor Überladung und Tiefentladung

Verpackungsdetails

Stückzahl pro Karton	1
Karton Volumen, m ³	0.076632
Kartongewicht, kg	25.06
Abmessungen Verpackung (LxBxH):	525x400x225 mm
Abmessungen Umkarton (LxBxH):	620x515x240 mm
Ursprungsland	CN
EAN Code	8716309087735
Zolltarif-Nr.:	8504408590

Lieferumfang

UPS
Power cord
USB cable
Software CD
Spare fuse

CE-Erklärung



Spezifikationen

UPS type: line interactive, pure sine wave
 Input: 220V AC $\pm$ 25%, 50Hz / 60Hz $\pm$ 10%
 Output: 220V AC $\pm$ 10%, 50Hz / 60Hz $\pm$ 0.5% (on battery)
 Output power factor: 0.8
 Inverter output efficiency (resistive load): 85%, any load type is allowed
 Switching time: no more than 10 ms (typically 6 ms)
 Backup time: 8...20 mins (depends on the load)
 Battery: 151 x 65 x 95 mm, sealed lead-acid 12 V / 9 Ah / 2.3 kg x 3 pcs
 Charge time: up to 12 hours
 Sockets: input IEC C14, outputs: Schuko EU type x 1 pc, IEC C13 x 6 pcs
 Operating conditions: 0°C~40°C, at humidity 10~90%RH non condensing
 Noise: < 45 dB (at 1 meter distance)
 Power: 2000 VA (1600 W)
 Dimensions: 440 x 410 x 132 mm
 Product weight: 19.8 kg
 "Cold-start" function

Systemvoraussetzungen

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.