

UPS Rack 2000VA

EG-UPSRACK-12

ULTIMATE DEFENCE

- Protects important data from power cuts
- Protects valuable equipment
- Protects users



Caratteristiche

- Regolazione automatica del voltaggio in output (AVR)
- Rack 3.4U metal case
- Interfaccia di controllo USB
- Display LCD
- Protezione da cortocircuiti
- Compatibile con generatori di potenza di tutti i brand
- Protezione contro i fulmini
- Allarmi visivi e sonori
- Protezione da sovraccarico e sottocarico

Confezione

Quantità per cartone, pezzi	1
Volume del cartone, CUM	0.076632
Peso del cartone, Kg	25.06
Individual package size LxWxH:	525x400x225 mm
Carton size LxWxH:	620x515x240 mm
Paese di origine	CN
Barcode	8716309087735
Customs code	8504408590

Contenuto della Confezione

UPS
Power cord
USB cable
Software CD
Spare fuse

Certificazioni



Specifiche

UPS type: line interactive, pure sine wave
Input: 220V AC $\pm$ 25%, 50Hz / 60Hz $\pm$ 10%
Output: 220V AC $\pm$ 10%, 50Hz / 60Hz $\pm$ 0.5% (on battery)
Output power factor: 0.8
Inverter output efficiency (resistive load): 85%, any load type is allowed

Switching time: no more than 10 ms (typically 6 ms)
Backup time: 8...20 mins (depends on the load)
Battery: 151 x 65 x 95 mm, sealed lead-acid 12 V / 9 Ah / 2.3 kg x 3 pcs

Charge time: up to 12 hours
Sockets: input IEC C14, outputs: Schuko EU type x 1 pc, IEC C13 x 6 pcs

Operating conditions: 0°C~40°C, at humidity 10~90%RH non condensing

Noise: < 45 dB (at 1 meter distance)
Power: 2000 VA (1600 W)
Dimensions: 440 x 410 x 132 mm
Product weight: 19.8 kg
"Cold-start" function

Requisiti di sistema

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.