

Rack UPS, 3000 VA, black

EG-UPSRACK-13

ULTIMATE DEFENCE

- Protects important data from power cuts
- Protects valuable equipment
- Protects users



Features

- Automatic output voltage regulation (AVR)
- Rack 3U metal case
- USB control interface
- LCD display
- Short circuit protection
- Compatible with power generators of any brand
- Overload, surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection

Packaging

Q'ty in crtn, pcs	1
Crtn volume, CUM	0.076632
Crtn weight, kgs	30.4
Individual package size LxWxH:	410x525x225 mm
Carton size LxWxH:	620x515x240 mm
Country of origin	CN
Barcode	8716309087742
Customs code	8504408590

Package contents

UPS
Power cord
USB cable
Software CD
Spare fuse

Certificates



Specifications

UPS type: line interactive, pure sine wave
 Input: 220V AC $\pm 25\%$, 50Hz / 60Hz $\pm 10\%$
 Output: 220V AC $\pm 10\%$, 50Hz / 60Hz $\pm 0.5\%$ (on battery)
 Output power factor: 0.8
 Inverter output efficiency (resistive load): 85%, any load type is allowed

Switching time: no more than 10 ms (typically 6 ms)
 Backup time: max. 5 40 mins (50 % -10 % load)
 Battery: 151 x 65 x 95 mm, sealed lead-acid 12 V / 9 Ah / 2.3 kg x 4 pcs

Charge time: up to 12 hours
 Sockets: input IEC C14, outputs: Schuko EU type x 1 pc, IEC C13 x 6 pcs

Operating conditions: 0°C~40°C, at humidity 10~90%RH non condensing

Noise: < 45 dB (at 1 meter distance)
 Power: 3000 VA (2400 W)
 Dimensions: 440 x 410 x 132 mm
 Product weight: 28.1 kg
 "Cold-start" function

System requirements

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.