


3DP-ABS3-01-TR

## ABS Filament Transparent, 3 mm, 1 kg

### VERSATILE & EASY TO USE

- Acrylonitrile butadiene styrene (ABS) is a common thermoplastic strong, flexible durable plastic available in a range of colors.
- ABS is the plastic used in lots of things around us and is perfect for heated plastic extrusion 3D printing.



### Features

- High strength, good toughness
- Low density: when printing larger volume the model is lighter
- Can be applied to a variety of 3D printers

### Specifications

Material: ABS, 3 mm diameter  
Weight: 1 kg/spool (2.2 lbs)  
Length: approx. 140 m  
Density at 21.5°C: 1.01 g/cm<sup>3</sup>  
Melt Flow Index at 10min, 2.16kg: 5  
Melt Point: 225 240 °C  
Heat-Deflection-Temperature at 0.455 MPa: 85 °C  
Yield Strength at 5mm/min: 45 MPa  
Impact Strength: 16 KJ/m<sup>2</sup>  
Elongation at Break: 30 %  
Diameter: 3.00 ± 0.05 mm  
Spool dimensions: 200 mm diameter x 67 mm height x 53 mm central hole

### Packaging

Q'ty in crtn, pcs	12
Crtn volume, CUM	0.048
Crtn weight, kgs	15.1
Individual package size LxWxH:	180x180x110 mm
Carton size LxWxH:	375x350x365 mm
Country of origin	CN
Barcode	8716309088855
Customs code	3916909000

### System requirements

A 3D printer with 3 mm extruder of temperature around 230 °, suitable for use with ABS filament

### Certificates

