

3DP-HIPS3-01-BS

# HIPS Filament Sky Blue, 3 mm, 1 kg

#### **VERSATILE & EASY TO USE**

- Practical liquid soluble HIPS material (High impact polystyrene) is a versatile, economical and impact-resistant support material.
- HIPS is soluble in Limonene and can be glued by acetone or superglue (Cyanoacrylate).
- Can be used as both standalone material and support material for over-lengths and holes in ABS parts.



# Specifications

Material: HIPS, 3 mm diameter Weight: 1 kg/spool (2.2 lbs) Length: approx. 140 m Density at 21.5?C: 1.04 g/cm3 Melt Flow Index at 10min, 2.16kg: 4

Melt Point: 225 240 ?C

Heat-Deflection-Temperature at 0.455 MPa: 7 ?C

Yield Strength at 5mm/min: 80 90 MPa

Impact Strength: 10 KJ/m2 Ensile Break: 55 % Diameter: 3.00 ± 0.05 mm

Spool dimensions: 200 mm diameter x 67 mm height x 53 mm central hole

## **Features**

- HIPS filament
- Maintains strength in high-impact applications
- Easily moldable, good dimensional stability and low volatility
- Suitable for use in a variety of 3D printers
- Can be easily glued and painted

## **Packaging**

Q'ty in crtn, pcs
Crtn volume, CUM
Crtn weight, kgs
Individual package size LxWxH:
Carton size LxWxH:
Country of origin
Barcode
Customs code

12 0.053 16 180x180x110 mm 380x375x370 mm CN 8716309089494 3916909000

## System requirements

A 3D printer with 3 mm extruder of temperature around 230 ?, suitable for HIPS filament

Do not remove 3D printed parts until they are fully cooled down

#### Certificates





