


# S/FTP Cat. 6A LSZH patch cord, red, 0.25 m

PP6A-LSZHCU-R-0.25M

- Perfect connection
- Dual shielded for a reliable connection
- Low Smoke Zero Halogen (LSZH) jacket
- Gold plated contacts



## Specifications

Category: category 6A  
 Type: SFTP (dual shielded)  
 Frequency bandwidth: Max. 500 MHz  
 Compliance with ANSI / TIA / EIA-568B standards  
 Conductor: AWG 27 (7 x 0.135 mm wire), CU  
 Conductor insulation: FM-PE 1.0 mm  
 Shielding: AL foil + braid shield (16 x 4/0.12 mm)  
 LDPE filler: yes  
 Polyester tape: yes  
 Drain wire: n/a  
 Jacket material: LSZH  
 Jacket braiding: n/a  
 Jacket outer diameter: 6.2 mm  
 Length: conform item description  
 Color: conform item description

## Features

- Patch cord with foil shielded pairs and braided cable, CAT 6A
- Gold plated contacts
- Low Smoke Zero Halogen (LSZH) jacket
- Molded strain reliefs
- Snagless boots

## Packaging

|                                |                |
|--------------------------------|----------------|
| Q'ty in crtn, pcs              | 500            |
| Crtn volume, CUM               | 0.041          |
| Crtn weight, kgs               | 10.48          |
| Individual package size LxWxH: | 150x120x10 mm  |
| Carton size LxWxH:             | 400x300x340 mm |
| Country of origin              | CN             |
| Barcode                        | 8716309091336  |
| Customs code                   | 8544421000     |

## Certificates

