



Flashforge PLA White, 1.75 mm, 0.6 kg

FF-3DP-PLA1.75-02-W

VERSATILE & EASY TO USE

- PLA (polylactide) is a biodegradable thermoplastic polyester, which is easy to print for variety 3D printers.
- It has no odor, a lower melting point and good flowability, no need to post-treatment.



Features

- High precision roundness enables higher printing quality
- No bubbles, vivid colors
- Can be applied to a variety of 3D printers
- 0.6 kg spool

Packaging

| | |
|--------------------------------|----------------|
| Q'ty in crtn, pcs | 20 |
| Crtn volume, CUM | 0.054 |
| Crtn weight, kgs | 19.35 |
| Individual package size LxWxH: | 195x195x60 mm |
| Carton size LxWxH: | 400x325x415 mm |
| Country of origin | CN |
| Barcode | 8716309091855 |
| Customs code | 3916909000 |

Specifications

Material: PLA, 1.75 mm diameter
 Weight: 0.6 kg/spool
 Density at 215°C: 1.24 g/cm³
 Melt Flow Index at g/10min, 190°C/ 2.16kg: 6
 Melt Point: 190 220 °C
 Heat-Deflection-Temperature at 0.455 MPa: 50 °C
 Yield Strength at 5mm/min: 62 MPa
 Impact Strength: 4.2 KJ/m²
 Ensile Break: 15 %
 Diameter: 1.75 ± 0.05 mm

System requirements

A 3D printer with 1.75 mm extruder of temperature around 200 °C, suitable for PLA filament

Certificates

