

# CAT6 UTP latiguillo

PP6U-3M/G

- Latiguillo de aluminio trenzado, cat6 AWG24, con protector de cables moldeados, conectores 50u" 8P8C, 3m



## Características

- CAT6 UTP latiguillo
- Tapas sin enganches

## Especificaciones

Category: category 6  
Type: UTP (unshielded)  
Frequency bandwidth: Max. 250 MHz  
Compliance with ANSI / TIA / EIA-568B standards  
Conductor: AWG 26 (7 x 0.15 mm wire), CCA  
Conductor insulation: HDPE 0.85 mm  
Shielding: n/a  
LDPE filler: yes  
Polyester tape: n/a  
Drain wire: n/a  
Jacket material: PVC  
Jacket braiding: n/a  
Jacket outer diameter: 6.2 mm  
Length: conform item description  
Color: conform item description

## Embalaje

|                                   |                |
|-----------------------------------|----------------|
| Cantidad por caja, pcs            | 100            |
| Volumen caja, M3                  | 0.04           |
| Peso caja, kgs                    | 7.84           |
| Medidas cajas individuales LxWxH: | 200x150x10 mm  |
| Medidas caja LxWxH                | 400x300x330 mm |
| País de origen                    | CN             |
| Código de barras                  | 8716309093224  |
| codigo de aduanas                 | 8544421000     |

## Certificados

