

3DP-ABS1.75-01-PP

ABS Filament Purple to Pink, 1.75 mm, 1 kg

VERSATILE & EASY TO USE

- Acrylonitrile butadiene styrene (ABS) is a common thermoplastic strong, flexible durable plastic available in a range of colors.
- ABS is the plastic used in lots of things around us and is perfect for heated plastic extrusion 3D printing.



Funkcijos

- High strength, good toughness
- Low density: when printing larger volume the model is lighter
- Can be applied to a variety of 3D printers

Packaging

Dėžių kiekis, vnt
Dėžių dydis, CUM
Dėžių svoris, kg
Individual package size LxWxH:
Kilmės šalis
Kilmės šalis
Brūkšninis kodas
Customs code

8
0.036
15.4
220x220x85 mm
440x440x185 mm
CN
8716309094689
3916909000

Techniniai duomenys

Material: ABS, 1.75 mm diameter
Weight: 1 kg/spool (2.2 lbs)
Length: approx. 400 m
Density at 21.5 °C: 1.01 g/cm³
Melt Flow Index at 10min, 2.16 kg: 5
Melt Point: 225 240 °C
Heat-Deflection-Temperature at 0.455 MPa: 85 °C
Yield Strength at 5mm/min: 45 MPa
Impact Strength: 16 KJ/m²
Elongation at Break: 30 %
Diameter: 1.75 ± 0.05 mm
Spool dimensions: 200 mm diameter x 67 mm height x 53 mm central hole

Sistemos reikalavimai

A 3D printer with 1.75 mm extruder of temperature around 230 °C, suitable for use with ABS filament

Sertifikatai

