

3DP-TPE1.75-01-B

TPE flexible filament Blue, 1.75 mm, 1 kg

VERSATILE & EASY TO USE

- Flexible filament is a special thermopolymer which allows the user to obtain materials similar to rubber. With this material, you can create objects that will appear as rubber itself, and according to the type of rubber, the user can obtain different levels of softness and elongation. The tear resistance characteristics of the material are excellent and resistance to tearing is high.



Features

- Unique flexibility
- High elasticity and excellent abrasion resistance
- Excellent build platform adhesion and bonding between layers

Specifications

Material: TPE, 1.75 mm diameter
Weight: 1 kg/spool (2.2 lbs)
Length: approx. 420 m
Density at 21.5 °: 0.9 g/cm³
Melt Flow Index at g/10min 200°C/5kg: 11
Melt Point: 190 240 °C
Heat-Deflection-Temperature: /
Yield Strength at 5mm/min: 43 MPa
Tear Strength: 86 KN/m
Elongation at Break: 500 %
Diameter: 1.75 ± 0.05 mm
Spool dimensions: 200 mm diameter x 67 mm height x 53 mm central hole

Packaging

Q'ty in crtn, pcs	8
Crtn volume, CUM	0.036
Crtn weight, kgs	10.89
Individual package size LxWxH:	210x210x85 mm
Carton size LxWxH:	440x440x185 mm
Country of origin	CN
Barcode	8716309095044
Customs code	3916909000

System requirements

A 3D printer with 1.75 mm extruder of temperature around 230 °C, suitable for TPE filament

Certificates

