UPS with AVR, 850 VA, 6 Schuko sockets, USB

EG-UPS-DT850U-01



ULTIMATE DEFENCE

- Table top design
- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use

Īpašības

- Uninterruptable 850 VA power supply with modified sine wave output
- Automatic AC voltage regulation (AVR)
- USB interface
- Intelligent surge-, overloadand short-circuit protection
- UPS battery backup
- Audible and visual alarms
- LED status indication
- Intelligent battery management with overcharge and over-discharge protection
- Wall mountable

Specifikācija

Type: line interactive
Waveform: sine wave (AC mains), modified (square) sine wave (battery)

Input: 220 V AC ± 25%, 50 / 60 Hz ± 10%
Output: 220 V AC ± 10%, 50 / 60 Hz ± 1% (220 V AC ± 5 % at inverter mode)

Switching time: less than 10 ms
Backup time: 10...30 mins (depends on the load)
Battery: 151 x 65 x 95 mm, sealed lead-acid 12 V DC / 8Ah
Charge time: up to 8 hours
Sockets: 1 x C13 (input), cable CEE 7/7P, 6 x Schuko (output)

Sockets with UPS: 6 pcs (3 backed up, all 6 surge protected)

Operating conditions: 0°C~40°C, at humidity 20~90%RH non condensing

Power: 850 VA (510 W)
Charging current: up to 1.2 A
Noise: < 45 dB at 1 m distance
Dimensions: 280 x 185 x 95 mm
Product weight: 5.6 kg
"Cold-start" function

Packaging

Skaits iepakojumā, gab.	3
Iepakojuma izmērs, kub.m	0.038786
Iepakojuma svars, kg	18.5
Individual package size LxWxH:	335x145x240 mm
Carton size LxWxH:	451x344x250 mm
Izcelsmes valsts	CN
Svītrkods	8716309098939
Customs code	8504408590

Iepakojuma saturs

UPS
Power cord
User manual

Sertifikāti

Sistēmas prasības

In order to work correclty, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.

Copyright © 2009–2024, Gembird Software Ltd.

Wittevrouwen 56 | 1358CD Almere | The Netherlands | Phone: +31-36-5211588
www.energenie.com | postmaster@energenie.com