

Noodstroomvoeding met AVR, 850 VA

EG-UPS-DT850U-01

- Praktisch compact tafelmodel met 6 stopcontacten
- Voorkomt dataverlies door stroomuitval
- De ideale bescherming voor alle gevoelige apparatuur
- Compact en betrouwbaar ideaal voor thuisof kleinzakelijk gebruik



Kenmerken

- Automatische 850 VA noodstroomvoorziening
- 6 stopcontacten, waarvan 3 met batterij-backupfunctie
- Automatische AC spanningsregelaar en stabilisator (AVR)
- USB aansluiting voor communicatie met PC
- Intelligente beveiliging tegen spanningspieken, overbelasting en kortsluiting op alle stopcontacten
- LED statusindicatie en hoorbaar en zichtbaar alarm bij stroomuitval
- Interne batterij met bescherming tegen overladen of teveel ontladen
- Mogelijkheid voor muurbevestiging

Verpakking

Verpakkingshoeveelheid/stuks	3
Volume doos/CUM	0.038786
Gewicht doos/kg	18.5
Afmetingen productverpakking LxBxH:	335x145x240 mm
Afmetingen transportverpakking LxBxH:	451x344x250 mm
Land van herkomst	CN
Streepjescode	8716309098939
Douanecode	8504408590

Inhoud verpakking

UPS
Netstroomkabel
USB-kabel
Software CD
Handleiding

Certificaat/Certificaten



Specificaties

Type: line interactive

Waveform: sine wave (AC mains), modified (square) sine wave (battery)

Input: 220 V AC $\pm 25\%$, 50 / 60 Hz $\pm 10\%$

Output: 220 V AC $\pm 10\%$, 50 / 60 Hz $\pm 1\%$ (220 V AC $\pm 5\%$ at inverter mode)

Switching time: less than 10 ms

Backup time: 10...30 mins (depends on the load)

Battery: 151 x 65 x 95 mm, sealed lead-acid 12 V DC / 8Ah

Charge time: up to 8 hours

Sockets: 1 x C13 (input), cable CEE 7/7P, 6 x Schuko (output)

Sockets with UPS: 6 pcs (3 backed up, all 6 surge protected)

Operating conditions: 0°C~40°C, at humidity 20~90%RH non condensing

Power: 850 VA (510 W)

Charging current: up to 1.2 A

Noise: < 45 dB at 1 m distance

Dimensions: 280 x 185 x 95 mm

Product weight: 5.6 kg

"Cold-start" function

Systeemvereisten

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.