

size: 90x160 mm



Pantone 116C



C70M50Y50K100



All brands and logos are registered trademarks of their respective owners.

NL

2-poorts USB auto-snellader: QC 3.0

Met ingebouwde beveiliging tegen te hoog voltage / stroom en kortsluiting

FR

Chargeur rapide de voiture USB 2 ports: spécification QC 3.0 avec sorties 5 V / 2.1 A et 12 V / 1.5 A

Système d'auto protection de courant

EN

2-port USB car quick charger: QC 3.0 specification with 5 V / 2.1 A and 12 V / 1.5 A outputs

Intelligent over-current, over-voltage and short circuit protection

DE

Dual-Port USB-Kfz Schnellladegerät, QC 3.0 Spezifikation mit 5 V / 2.1 A und 12 V / 1.5 A Output

Intelligenter Überstrom-, Überspannungs- und Kurzschlusschutz

Specifications

Input voltage: 12 V - 24 V DC

USB output 1: 5 V, 2.1 A (max.)

USB output 2: QC 3.0; 3.6 V - 6.5 V,

6.5 V - 9 V, 2 A / 9 V - 12 V, 1.5 A (or 5 V, 2.1 A)

Dimensions: 25 mm x 25 mm x 58 mm

Net weight: 27 g



Made in China

P/N JB-U2QC3-CAR-01



www.jb-connect.nl | helpdesk@jb-connect.nl
1358 CD, Almere, The Netherlands | 0900 - 4362473 (gratis in NL)