Actual package may differ from this package preview.
No rights can be derived from this document.

KVM SWITCH

GEMBIRD®

- ENABLES ONE SET OF KEYBOARD/MONITOR/MOUSE TO CONTROL 2 COMPUTERS
- SUITABLE FOR ANY OPERATING SYSTEM



WORLD OF IDEAS

GEMBIRD®

KVM SWITCH

FEATURES

- PS/2 (AT) keyboard and mouse emulation
- Switching of the PCs stereo audio channels
- Optional SwitchSound mode - switching of the PCs stereo audio channels
- Additional buzzer and LED indication of the sound event
- Optional HoldSoundEvent mode – indication of the sound event will be continued until the channel is selected
- Plug and Play keyboard and mouse initialization
- Hot-plug connection of the computers without need to reboot
- Standard PS/2 mouse, 3-buttons, scrolling wheel, Microsoft®, Logitech®, A4Tech®, Genius® 4-5 buttons mice support
- Keyboard LEDs status saving and restoring
- Mode and event LED indication
- Computer boot-up LED indication
- PC switching via front panel pushbuttons or keyboard hot keys
- AutoScan mode with intervals 4, 10, 30 secs
- Optional automatic inactive computer sleeping mode blockage
- Video resolution up to 2048 x 1536, video bandwith 250 MHz, DDC, DDC2, DDC2B
- No software required

EIGENSCHAFTEN

- Gestattet die Bedienung von zwei Servern oder Workstations von einer Bedienenheit aus (Tastatur, Bildschirm und Maus)
- Geld und Platz sparen in einem Multi-Computer-Umfeld
- Intelligente Emulation einer PS/2-Tastatur und -Maus
- Plug-and-Play-Tastatur und -Maus mit automatischer Initialisierung
- Hotplug-Verbindung der Computer – kein Neustart notwendig
- Zusätzliche Funktion: automatische Blockierung des Standby-Modus bei einem inaktiven Computer
- Standard-PS/2-Maus, 3 Mausstasten, Mausrad, Unterstützung von Mäusen mit 4 bis 5 Tasten von Microsoft®, Logitech®, A4Tech® oder Genius®
- LED-Anzeige auf der Tastatur für Speichern und Wiederherstellen
- LED-Anzeige für Modus und Event
- Umschalten zwischen PCs über Druckstasten an der Vorderseite oder Hotkeys auf der Tastatur
- Autoscan-Modus mit Intervallen von 4, 10, 30 Sekunden
- Video-Auflösung bis zu 2048 x 1536, Videobandbreite 250 MHz, DDC, DDC2, DDC2B
- Keine Software erforderlich

SPECIFICATIONS

- Number of switching computers: 2
- Mouse and keyboard protocol emulation: PS/2 keyboard, PS/2 mouse, PC/AT keyboard
- Case design: Desktop
- Case housing: Metal with plastic front panel
- Computer selection: Push buttons or keyboard hot keys
- Computer side connectors: HD-15M x 2, MD-6F x 4, 3.5 mm stereo audio jack x 2
- Console side connectors: HD-15M x 1, MD-6F x 2, 3.5 mm stereo audio jack x 1
- Front panel LEDs

SYSTEM REQUIREMENTS

Console requirements:
- VGA, SVGA, or Multisync monitor supporting the highest resolution among all the PCs connected to the switch
- PS/2 compatible mouse
- PS/2 compatible keyboard

Computers requirements:
- VGA, SVGA or Multisync video card
- 6-pin mini-DIN (PS/2) mouse port
- 6-pin mini-DIN (PS/2) keyboard port

Cables:
- Male-to-male VGA cables
- Male-to-male Mini-DIN 6 pin cables
- Male-to-male 3.5 mm stereo plug audio cables

GEMBIRD®
SHAPING THE PERFECTION
GEMBIRD EUROPE B.V.
WWW.GEMBIRD.EU

MADE IN CHINA

PART NUMBER

CAS-241

8 717630 902207

All brands and logos are registered trademarks of their respective owners.

size: 155x55x145 mm

Pantone 877C

C:0 M:100 Y:100 K:0

100% black