Actual package may differ from this package preview.
No rights can be derived from this document.

GEMBIRD®

AUTOMATIC CPU AND AUDIO SWITCH FOR 4 COMPUTERS WITH POWER MANAGEMENT

GEMBIRD®

- ENABLES ONE SET OF KEYBOARD/MONITOR/MOUSE TO CONTROL 4 COMPUTERS
- ALLOWS TO SWITCH THE ATTACHED PCS ON AND OFF
- COMPUTERS SELECTABLE BY MEANS OF A PUSH BUTTON OR KEYBOARD HOT KEYS
- ALSO SWITCHES AUDIO
- SAVE SPACE AND MONEY IN MULTI-COMPUTER ENVIRONMENTS
- SUITABLE FOR ANY OPERATING SYSTEM



WORLD OF IDEAS

GEMBIRD®

AUTOMATIC CPU AND AUDIO SWITCH FOR 4 COMPUTERS WITH POWER MANAGEMENT

FEATURES

- In combination with SIS-PM-841 allows to turn the attached servers on and off
- Switching of the PCs stereo audio channels
- Optional SwitchSound mode - switching of the PCs stereo audio channels
- Additional buzzer and LED indication of the sound event
- Optional HoldSoundEvent mode – indication of the sound event will be continued until the channel is selected
- Plug and Play keyboard and mouse initialization
- Hot-plug connection of the computers without need to reboot
- PC switching via front panel pushbuttons or keyboard hot keys
- No software required

EIGENSCHAFTEN

- Gestattet die Bedienung von zwei Servern oder Workstations von einer Bedienenheit aus (Tastatur, Bildschirm und Maus)
- Geld und Platz sparen in einem Multi-Computer-Umfeld
- Umschalten des Audiokanals des PCs
- Zusätzliche Funktion: automatisches Umschalten zu dem PC, bei dem ein Audioevent auftritt; zusätzlicher Summer und LED-Anzeige des Audiosignals
- Plug-and-Play-Tastatur und -Maus mit automatischer Initialisierung
- Hotplug-Verbindung der Computer – kein Neustart notwendig
- Umschalten zwischen PCs über Druckstasten an der Vorderseite oder Hotkeys auf der Tastatur
- Keine Software erforderlich

KENMERKEN

- Hiermee kunt u vanuit één console (toetsenbord, monitor en muis) twee servers of werkstations bedienen
- Besparr ruimte en geld in omgevingen met verscheidene computers
- Omschakeling van het audiokanaal van de pc
- Optie om automatisch over te schakelen naar de pc waar het geluid zich voordoet. Extra zoemer en controlelampje om de geluidsgebeurtenis te melden
- Plug-and-Play initialisatie van het toetsenbord en de muis
- Hot-plug aansluiting van de computers zonder ze te moeten herstarten
- PC-overschakeling via drukknoppen op voorpaneel of sneltoetsen op het toetsenbord
- Geen software vereist

XAPAKTEPИСТИКИ

- Дает возможность управлять 4 серверами или рабочими станциями с одной консоли (клавиатура, монитор, мышь)
- Экономит место и деньги в многокомпьютерных системах
- Переключение аудио стереоканалов
- Индикация и передача звуковых событий с нажатиных каналов
- Не требует перезагрузки при подключении мышии и клавиатуры
- Не требует перезагрузки компьютеров при их подключении
- Управление переключением каналов с лицевой панели
- Не требует программного обеспечения

SPECIFICATIONS

- Number of switching computers: 4
- Mouse and keyboard protocol emulation: PS/2 keyboard, PS/2 mouse, PC/AT keyboard
- Case design: Desktop
- Case housing: Metal with plastic front panel
- Computer selection: Push buttons or keyboard hot keys
- Audio channels type: Stereo
- Audio frequency ban
- Computer side connectors: HD-15Mx4, MD-6Fx8, 3.5 mm stereo audio jack x 4
- Console side connectors: HD-15Mx1, MD-6Fx2, 3.5 mm stereo audio jack x 1
- Power management interface: RJ45 connector for CAT5 twisted pair patch cord connected with SIS-PM-841 surge protector
- Front panel LEDs per channel: "Link/Event", "Active/Scan"
- Standard PS/2 mouse, 3-buttons, scrolling wheel, Microsoft®, Logitech®, A4Tech®, Genius® 4-5 buttons mice support
- Keyboard LEDs status saving and restoring
- Mode and event LED indication
- AutoScan mode with intervals 4,10,30 secs
- Video resolution up to 2048x1536, video bandwith 250 MHz, DDC, DDC2, DDC2B
- Computer boot-up LED indication

SYSTEM REQUIREMENTS

- For the power management: SIS-PM-841 programmable remote controllable surge protector

CONSOLE REQUIREMENTS:

- VGA, SVGA, or Multisync monitor supporting the highest resolution among all the PCs connected to the switch

COMPUTERS REQUIREMENTS:

- PS/2 compatible keyboard
- PS/2 compatible mouse
- VGA, SVGA or Multisync video card
- 6-pin mini-DIN (PS/2) mouse port
- 6-pin mini-DIN (PS/2) keyboard port

CABLES REQUIRED:

- Male-to-male VGA cables
- Male-to-male Mini-DIN 6 pin cables
- Male-to-male 3.5 mm stereo plug audio cables

PART NUMBER

CAS-441-PM

8 716309 047937

SHAPING THE PERFECTION

GEMBIRD EUROPE B.V.
WWW.GEMBIRD.EU

RoHS

MADE IN CHINA

All brands and logos are registered trademarks of their respective owners.

CAS-441PM
size: 240x145x54 mm

Pantone 877C

C:0 M:100 Y:100 K:0

100% black